

FC1-TA AURORA TRIPLE ACTION FLYWHEEL CYCLE



If you require more information on products or availability, please contact using details below.

Frame	Combination 60mm x 30mm Oblong and 50mm Diameter Round Tubular Steel Main Frame. 25mm Square Handlebar Uprights and 25mm Diameter Round Tubular Steel Handlebars.
Frame Support	Grey Coloured Fixed Front Frame End Caps. Twist-Adjust Rear Frame End Caps.
Frame Finish	Chip Resistant White Coloured Epoxy Powder Coated.
Cycle Action - Single/Dual/Triple	Triple Action with Twin Independent Hydraulic Cylinders Rated at 40 PSI.
Drive System – Chain/Belt	Standard Chain with Freewheel Drive.
Resistance System	7kg Balanced Cast Iron Flywheel. Polypropylene Friction Tape with Felt Backing.
Resistance Adjustment	Grey Coloured Micro Tension Controller.
Handlebars	Grey Coloured Contoured, Smooth Expanded Foam Padded Grips.
Saddle	Grey Coloured Expanded PU with Triangular Base Plate Fitting.
Saddle Stem Cover	Grey Coloured 46-Fluted Extruded PVC.
Saddle Height Adjustment	Grey Coloured Threaded Knob. 6-Position Adjustment. Minimum Height 67cm. Maximum Height 89cm.
Pedals	Grey Coloured, Self-Presenting with Velcro Style Adjustable Footstraps.
Exercise Monitor	Grey Coloured, 5-Function with Calorie (Theoretical Calorie Burn), Distance (Miles), Scan, Speed (mph), and Time (Minutes / Seconds) Modes.
Assembled Dimensions	L 82cm x W 50cm x H 127cm x Wt 22.5kg
Packed Dimensions	L 70cm x W 23cm x H 65cm x Wt 24.5kg