


HR2 HERMES HYDRAULIC ROWING MACHINE



If you require more information on products or availability, please contact using details below.

Frame	Combination 80mm x 40mm Oblong and 38mm Diameter Round Tubular Steel Main Frame. 25mm Round Tubular Steel Row Arms.
Frame Support	Black Coloured Sit-Flat Frame End and Support Caps.
Frame Finish	Chip Resistant Black Coloured Epoxy Powder Coated.
Rowing Action - Single/Sculling	Single Action.
Resistance System	Twin Independent Hydraulic Cylinders Rated at 42 PSI.
Resistance Adjustment	Black Coloured Hydraulic Cylinder Adjuster Clamps.
Row Arms	Deep Chromed, Contoured, with Smooth Expanded Foam Padded Grips.
Seat	Black Coloured PVC Cover over Expanded Foam.
Seat Carriage	Pressed Mild Steel with Composite Bearing Mounted Upper Seat Rollers and Composite Lower Seat Guide Rollers.
Footplates	Black Coloured PVC with Adjustable Velcro Style Footstraps.
Exercise Monitor	5-Function, 3 Button with Calories, Counter, Distance, Tempo and Timer Modes
Assembled Dimensions	L 118cm x W 73cm x H 17cm x Wt 14kg